

Stock Colors



Brown



Cola



Desert Tan




Dark Walnut



English Red



Light Green



Gray



Leather



Malay Tan



Saddle Brown




Terra Cotta



Vintage Umber


Special Order Colors



Black



Blue



Dark Blue



Fern Green



Burnt Orange



Purple



Red



Turquoise

NOTE: It is highly recommended that you do a sample test area before installation. The color samples shown are approximate and represent as closely as possible the appearance of COHILLS PRO SERIES® UV STABLE CONCRETE DYE. The final color of the concrete may not match the colors shown here due to variables beyond our control including finishing techniques, job conditions & curing methods. For additional information see technical bulletin.

APPLICATION TIPS:

PREPARATION: Make sure the area to be dyed is clean and free from all forms of dirt, oil, alkali, paint, cure & seal and any other form of contaminants. Cohills Pro Series® UV Stable Concrete Dye should be applied only to dry/neutral concrete surfaces. A sample should be done on the actual surface of the proposed application. Doing this in several areas will help determine suitability, coverage and approximate final results.

MIXING: Cohills Pro Series® UV Stable Concrete Dye is packaged in a liquid form. Shake bottle well and pour contents into 1 gallon of acetone (tip: pour a small amount of acetone into the dye container and shake to remove any remaining dye). Shake well for 30 seconds. **DO NOT USE ANY FORM OF ELECTRICAL EQUIPMENT WHEN MIXING DYE WITH ACETONE.** Follow all acetone instructions and refer to MSDS for exposure limitations and safe handling procedures.

APPLICATION: Using a high quality acetone sprayer, apply Cohills Pro Series® UV Stable Concrete Dye in a uniform circular motion keeping spray tip approximately 24 inches from the surface. **DO NOT ALLOW DYE TO PUDDLE.** Allow surface to dry approximately 5-10 minutes. If applying a second coat, clean spray nozzle & tip and repeat steps for first coat.

CLEANING: THERE IS NO CLEANING OR BUFFING REQUIRED BETWEEN APPLICATION OF DYEING AND SEALING.

SEALING: Using a low viscosity sprayable sealer, apply a thin even coat (use the appropriate sprayer and tip per sealer instructions) **IT IS NOT RECOMMENDED TO ROLL ON THE FIRST COAT OF SEALER AS IT MAY REACTIVATE THE DYE.** Two coats are recommended for superior protection. If applying a floor finish/wax over the sealer, allow 4-5 days for sealer to cure before applying. Follow floor finish/wax manufacturer's instructions.

Approximate coverage rates: 250 sq. ft.-400 sq. ft

Coverage rates above reflect approximate coverage of finished product (per gallon) applied per instructions. Coverage rates will vary with porosity of the concrete, temperature and application. For additional information see technical bulletin.

Distributed by: Coatings Hub

(833) 3-COAT IT

service@coatingshub.com

coatingshub.com